

## One Way Shut-Off - Series 2 thru 6



#### Features:

- · High flow metal valves.
- Precision molded seals form a "bubble tight" seal for reliable operation within rated working pressures. Nitrile (Buna-N) seals are standard. EPDM, Viton and Neoprene seals are available as options.
- Proven ball locking mechanism with large numbers of stainless steel locking balls evenly distribute the load to resist wear and provide positive connections and allow a swiveling action to reduce hose torque.
- Integral sleeve guard protects the sleeve and resists accidental disconnects for the "SG" series.
- Knurling and/or grooves on the sleeve provide a gripping surface for ease of operation.
- Wide range of body sizes, materials, options and end terminations are available to meet specific needs.
- Accepts Industrial Interchange Plug.



**Operation:** Sleeve type couplings are widely used to connect air and low pressure fluid lines. Their compact and economical design uses a ball locking mechanism consisting of captive stainless steel balls that engage the locking groove on the mating plug. The sliding spring loaded sleeve on the socket must be manually retracted in order to connect or disconnect the plug.

Material: Brass body and socket end, zinc-plated steel sleeve Working Pressure: 300 PSIG; vacuum to 26" Hg Interchangeability: Complies with ANSI/NFPA T3.20.14-1990 & ISO 6150-B

Considerations	Body Size			
Specifications	1/4"	3/8"	1/2"	
Rated Pressure (psi)	300	300	300	
Temp. Range (Buna-N Seal) -40° to +250° F		F		
Locking Device	Stainless Steel Balls			
Vacuum Data (inches Hg)				
Disconnected (coupler only)	Not Recommended			
Connected	27.4 27.4 27.4			
Approximate CFM at 100 (psi)	37	70	150	

# 1/8" One Way Shut-Off - 2 Series

### 2 Series 1/8" Plugs

c and Tubing	
# <u> </u>	
Plas Meta	(SSIN)



		Part No.	FPT	Description
emale hread	Female Thread	23-2	1/8"	Steel
шH		27-2	1/4"	Steel

		Part No.	MPT	Description
le ad	Male Thread	22-2	1/8"	Steel
Ma hre		22-2B	1/8"	Brass
		22-2S/S	1/8"	303 Stainless
		24-2	1/4"	Steel

	Part No.	I.D.	Description
ose tem	02-2	1/8"	Steel
₹\$	03-2	<sup>3</sup> / <sub>16</sub> "	Requires Hose Clamp
	04-2	1/4"	(See page 96 for typical hose clamps)

		Part No.	I.D. x O.D.	Description
able Slamp		PB3-2	<sup>1</sup> /4" <b>x</b> <sup>1</sup> /2"	
Reusab Hose Cla	TO THE PARTY OF TH	PB5-2	½" x ½""	Steel
工	FOSTER D	PB7-2	<sup>1</sup> / <sub>4</sub> " x <sup>5</sup> / <sub>8</sub> "	

**- 10 -** www.zsi-foster.com



# <sup>1</sup>/<sub>8</sub>" One Way Shut-Off - 2 Series



### 2 Series 1/8" Sockets

	Part No.	Size	Description	
ic and Tubin	SJ8-2	.170" x ½"	Plastic	
	BLSJ8-2	.17U X /4	Ball Lock, 1/4" Plastic	
ast	ast tal	SJ8-2M		Soft Metal
Mei	BLSJ8-2M	1/4""	Ball Lock, Soft Metal	
	U	SJ8-2S/S		303 Stainless

gu		Part No.	Size	Description
iqn		SJ8P-2	.170" x ½" -	Plastic
al T		BLSJ8P-2		Ball Lock, Plastic
Met el Mc		SJ8P-2HW		Plastic for Hot Water
ब्रे ४०		SJ8P-2W		Plastic, for Water
asti	Plastic P	SJ8P-2M		Soft Metal
Ē		BLSJ8P-2M		Ball Lock, Soft Metal

		Part No.	FPT	Description
		2302		Brass/Steel
		BL2302		Ball Lock
		2302H		Brass/Steel For Heat, Viton Seal
<u> 5</u>		2302HW	1/8"	Brass/SS For Hot Water, Viton Seal
ē	CO	2302S/S	/8	303 Stainless
L L	WEST TO SERVICE STATE OF THE PERSON NAMED IN COLUMN TO SERVICE STATE OF THE PERSON NAMED STATE OF THE SERVICE STATE OF THE PERSON NAMED STATE OF THE SERVICE STATE OF	BL2302S/S		Ball Lock, 303 Stainless
Female Thread	1000	2302S/SH		303 Stainless For Heat, Viton Seal
Fen		2302W		Brass/SS For Water, Buna-N Seal
		2702		Brass/Steel
		BL2702		Ball Lock
		2702H	1/4"	Brass/Steel For Heat, Viton Seal
		2702HW		Brass/SS For Hot Water,Viton Seal

		Part No.	MPT	Description
		2202		Brass/Steel
		BL2202		Ball Lock
	10000	2202S/S		Brass
ad		BL2202S/S		Ball Lock, 303 Stainless
Thre	2202H 1/8" 2202S	2202H	1/8"	For Heat, Viton Seal
Male Thread		For Steam, Brass/SS, EPDM Seal		
		2202W		For Water, Brass/SS, Buna-N Seal
		2402		Brass/Steel
		BL2402	1/4"	Ball Lock
		2402H		For Heat, Viton Seal

		Part No.	I.D.	Description
		2022		Brass/Steel
		BL2022	1/8"	Ball Lock
	F (C)	2022W	7.6	For Water, Brass/SS, Buna-N Seal
Ε	MD., 246	2032		Brass/Steel
Ste		BL2032	<sup>3</sup> / <sub>16</sub> "	Ball Lock
Hose Stem	2622	2032HW		For Hot Water, Brass/SS, Viton Seal
Ĭ		2032S		For Steam, Brass/SS, EPDM Seal
		2042		Brass/Steel
	BL2042 2042HW	1/4"	Ball Lock	
		2042HW	,4	For Hot Water, Brass/SS, Viton Seal
	Requires Hose C	Clamp (See page 9	96 for typi	cal hose clamps)

Non-Standard Product Standard Product

See page 138 for full size templates