



SVPC Series Safety Vent Couplers (Industrial Interchange)

Hose Barb		Part No.	Body	Hose ID	Description
		SVPCA62.R	3/8"	3/8"	Fully Protective Cover*, for Rubber Hose
		SVPCA62.P		3/8"	Fully Protective Cover*, for Poly Hose
		SVPCA72.P		7/16"	Fully Protective Cover*, for Poly Hose
		SVPC262.R	1/2"	3/8"	Fully Protective Cover*, for Rubber Hose
		SVPC262.P		3/8"	Fully Protective Cover*, for Rubber Hose
		SVPC272.P		7/16"	Fully Protective Cover*, for Poly Hose

Requires Hose Clamp (See page 96 for typical hose clamps)


* All SV, SVPC Sockets feature a Silicone-free assembly.

See page 140 for full size templates


Hose Barb with Strain Relief		Part No.	Body	Hose ID	Description
		SVPCA66.R	3/8"	3/8"	Fully Protective Cover*, w/Strain Relief for Rubber Hose
		SVPCA66.P		3/8"	Fully Protective Cover*, w/Strain Relief for Poly Hose
		SVPCA76.P		7/16"	Fully Protective Cover*, for Poly Hose
		SVPC266.R	1/2"	3/8"	Fully Protective Cover*, w/Strain Relief for Rubber Hose
		SVPC266.P		3/8"	Fully Protective Cover*, w/Strain Relief for Rubber Hose
		SVPC276.P		7/16"	Fully Protective Cover*, for Poly Hose

Requires Hose Clamp (See page 96 for typical hose clamps)

Protective Covers

Protective Cover for "SV4" Sockets		Part No.	Size	Description
		SV4-PC	3/8"	Plastisol Rubber

- Superior cushioning effect of Plastisol cover provides better protection for auto, motorcycle, marine, & appliance finishes.
- Flexible protective cover allows normal coupling operation while reducing the entry of contaminants in dirty environments.
- Standard SV couplers with protective covers are less expensive than competitive hard plastic models.

Protective Cover for "SV5" Sockets		Part No.	Size	Description
		SV5-PC	1/2"	Plastisol Rubber

- Superior cushioning effect of Plastisol cover provides better protection for auto, motorcycle, marine, & appliance finishes.
- Flexible protective cover allows normal coupling operation while reducing the entry of contaminants in dirty environments.
- Standard SV couplers with protective covers are less expensive than competitive hard plastic models, plus they eliminate the need to stock both standard and plastic bodied couplers.

Push-Button Safety Vent Series

Zero Pressure Connect and Disconnect Design

Features:

- Industrial Interchange, Pneumatic Application
- Anodized Aluminum Body for long life
- Swivel body to keep hose untangled
- Push twice for release. First push vents, second releases
- Button, Valve & Venting Ring: Hardened zinc plated steel
- Springs, Balls: Stainless Steel
- ISO 4414 Norm
- Flow capacity: 37SCFM (at 90 psi with connected insert)
- Max working pressure: 175 psi (safety factor 4:1)
- Recommended working Temperature: 0°F-160°F

Female Pipe Thread Industrial Interchange		Part No.	Size	Description
		SPB3003	1/4"	1/4" Body, Safety Push Button
SPB4204	3/8"			

Male Pipe Thread Industrial Interchange		Part No.	MPT	Description
		SPB3103	1/4"	1/4" Body, Safety Push Button
SPB4304	3/8"			

Note: Foster approved components (May be imported)